



WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

Auto Edge Banding Machine ECO F7 (EB-295)



Machine Functions:















Pre-milling

Gluing

End-cutting

Fine-trimming (

Corner-trimming

Scrapping

Buffing

Machine Technical Data:

Pre-milling motor power: 1.8kw*2 Gluing motor power: 0.75kw

Heating power: 1.5kw

Ending trimming motor power: 0.37kw*2 Fine trimming motor power: 0.75kw*2 Corner trimming motor power: 0.75kw

Buffing motor power: 0.37kw*2

belt motor power: 1.5kw

Working speed: 8-11-13 m/min

Max edge height: 45mm Panel thickness: 10-45mm

Edge banding tape thickness: 0.4-3mm

panel width: 80mm

Working air pressure: 0.6-0.8Mpa packing size: 4280*650*1280mm

weight:1230kg







WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

Functions of Machine:

1. Control system: delta

PLC overall equipment control;

7" industrial touch screen display;

All kinds of safety protection reminders.



2. Tool conveying

Abrasion resistant conveying block;

The semi-circular guide rail is precisely guided and hardened to improve wear resistance;

The conveying motor is started by **frequency** conversion, the starting is stable, and the braking system is provided.



3. Pressure beam device

Thickened aluminum alloy profile compression beam.







Qingdao Jiakemu Machinery Manufacture CO.,LTD
WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

4. Safety device: Honeywell brand

The equipment complies with relevant national standards;

The cylinder limits the spacing of the feed plates to protect the normal operation of each component.



5. Pre-milling

With diamond milling cutter. The edge after milling is straight and smooth, which is conducive to the accuracy of subsequent processes



6. Gluing

The glue mechanism adopt a special structure to gelatinize the plates and coating materials uniformly, ensure a more solid conglutination.









WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

7. End cutting

Conventional single guide rail before and after the same head device, high reliability, high efficiency.



8. Fine trimming

Two motors:

Two fine milling cutters,

Specification: (arc radius R2, 4Z);

Equipped with independent vacuum hood.



9. Corner-trimming

Specification: (arc radius R2, 4Z);

Make the corner more smooth and rounde.









WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

10. Scrapping

Smooth the edges and removing residual adhesive lines



11. Buffing

The buffing device adopt the board processed by cotton polishing wheel, by end polishing to make a more smooth surface.



12. Electrical Equipment: Delta brand

380V input voltage;

Independent Variable-frequency Drive control with motor brake function;

Phase sequence protection device;

Equipment and electrical appliances comply with relevant national standards.







WEST OF NO. 2 TIANSHAN ROAD TONGJI SUB-DISTRICT JIMO-CITY QINGDAO CHINA 266200

Tel: +86 15063045902 +86 13553051579

Website: sicarwood.com jiakemu.com E-mail: info@sicarwood.com

13. Low-voltage components

Main low-voltage components adopt **Siemens** brand to ensure stable and durable operation of equipment



14. Major parts and components adopt high quality famous brand products.

